


# STOBITEX - PU Colour-Coded Protection Sleeves according to DIN EN 1492-1/2



- High structural rigidity
- High resistance to abrasion
- Extremely cut resistant
- Very good elasticity
- Good chemical resistance
- Very good recognition
- The best protection for double layer slings



Now the proven STOBITEX PU Protection Sleeves are also available coloured-coded for 2 layer webbings from 1 – 10 tons. Colours meet DIN EN 1492-1/2 for marking the load capacity of 2 layer webbings up to 10 tons.

Advantage: because of the colour, the load capacity of the retracted webbing is clearly visible from afar. This provides better safety for the person attaching it.

The risk of using unsuitable webbings is reduced.

Name	For 2 layer lifting belts	Weight bearing capacity	Weight per m single-sided	Weight per m double-sided	1 sided use of glass fibre available*
<b>STOBITEX PU Protection Sleeve</b>	[mm]	(to)	Kg	Kg	
<b>a / i / h / w</b>					
50/40/10/5	30 mm	1	0,85	1,10	Yes
80/70/12/5	60 mm	2	1,30	1,60	Yes
110/100/12/5	90 mm	3	1,55	2,10	Yes
145/135/12/5	120 mm	4	2,00	2,80	Yes
170/160/12/5	150 mm	5	2,30	3,40	Yes
200/190/12/5	180 mm	6	2,60	3,80	Yes
260/250/20/8	240 mm	8	3,80	5,60	Yes
330/320/15/8	300 mm	10	4,40	7,20	yes

**Note:**

the coloured fabric is partially covered on the effective area due to the use of glass fibre.

The sides are still highlighted in colour.

The technical details are the same as the standard protection sleeves.

All sizes are approximate! Techn. changes reserved