

STOBITEX - PU Sharp Edge Protection Plates "DF"



STOBITEX PU-Elastomer sharp edge protection plates "DF" can be used wherever there are sharp edges to be protected or where damage to lifting materials needs to be prevented. The protective plates are applied during the load fastening / lashing operation. The lashing belt is threaded through the two openings, so that the plate can slide freely along the belt. During the lashing process the belt can thus slide over the plate, avoiding damage due to no direct contact between the belt and sharp edges. The minimum plate thickness "d" recommended to afford good cut protection is 4 mm.

Plates can be supplied in all sizes Standard sizes are listed in the table.

Name	Length *Width (mm)	Recess a * b (mm)	Weight per unit approx.
DF 25	250 * 80	25 * 10	0,11 Kg
DF 35	250 * 80	35 * 10	0,12 Kg
DF 55	300 * 100	55 * 10	0,17 Kg
DF 60	450 * 100	60 * 30	0,26 Kg
DF 70	450 * 120	70 * 30	0,30 Kg
DF 80	450 * 120	80 * 30	0,31 Kg
DF 90	470 * 130	90 * 40	0,33 Kg
DF 110	470 * 150	110 * 40	0,40 Kg
DF 130	470 * 170	130 * 40	0,43 Kg
DF 160	470 * 200	160 * 40	0,48 Kg
DF 200	470 * 240	200 * 40	0,54 Kg
DF 220	470 * 240	220 * 40	0,57 Kg
DF 250	500 * 280	250 * 40	0,70 Kg
DF 320	600 * 400	320 * 40	1,33 Kg
DF 420	600 * 500	420 * 40	1,93 Kg

Layer thickness d approx. 5 mm

Other sizes on request.

All sizes are approximate!

Techn. changes reserved.

Stockmeier & Nauer Kunststofftechnik
GmbH & Co. KG
Zeppelinstr. 16
32051 Herford
GERMANY
Tel.+49/05221/9265-0 Fax: - 10